

CATCH

26443-450

26443-Brass
26450-Nickel

FEATURES:

- base metal of steel with nickel or brass finish over copper undercoat
- has sturdy guarded drawbolt with crimped wire loop
- bottom section has 3 holes for attachment with rivets or screws
- round head screws supplied - 1/2" x #5
- top section has 2 holes for attachment by rivets or screws
- surface mounted
- non-locking

APPLICATION:

A drawbolt catch for securing the lids of wood, metal or plastic boxes.

SPECIFICATIONS:

Drawbolt

A sturdy guarded drawbolt which has a crimped wire loop, three rivet holes in bottom section. Also in plain steel, not hole for spot welding.

INSTALLATION:

Introduction - Smaller boxes may only need one (1) catch and larger boxes normally uses two (2) catches.

1. Drawbolt top and bottom catch together.
2. Place catch on front of box straddling lid and main box meeting line. Position in center for a single catch and space out to sides for two (2) catches. 1-1/2" to 2" from box ends.
3. While holding catch in correct position mark mounting holes with pencil.
4. Drill pilot holes in wood for mounting catches on a wooden box and then attach with wood screws provided.

Note: If catch is to be mounted to a metal or plastic box, then use pop rivets for attachment. Drill pilot holes and attach catch with the 1/8" pop rivets of the appropriate length.

