

- 62315 - 50" Oak lead strip w/cable
- 62323 - 50" Oak tambour slat
- 62331 - 24" Oak lead strip w/cable
- 62349 - 24" Oak tambour slat
- 81349 - 60" Oak lead strip w/cable
- 81331 - 60" Oak tambour slat

FEATURES:

- comes in 24", 50" or 60" lengths
- tambour lead strips come with 30" long cables
- cables are located 7" from each end' 24" strips have 2 cables; 50" and 60" strips have 3 cables (center cable is 3" off center)
- slats are sold individually and are predrilled to accept cable
- slats have an interlocking design to help keep them in line and inhibit warping
- superior design for double curve applications
- slats measure 5/8" thick x 27/32" wide (3 slats per 2-1/2" width)
- lead strips measure 3/4" thick x 2-1/4" wide
- available in oak only
- minimum convex curve of 2" radius' minimum concave curve of 2" radius

APPLICATION:

This free flowing cable supported tambour design allows for making customized tambour doors for desks and entertainment centers. This is a superior design for using on double curve applications.

SPECIFICATIONS:

3 Slats per 2-1/2"
Lead strips come with
30" cables located 7"
from edge.

24" has two cables.
50" and 60" have three cables.
(center cable is located 3" off center)

