

# MATERIAL SAFETY DATA SHEET

## Klean Strip Green Denatured Alcohol

Page: 1

HEALTH	1
FLAMMABILITY	3
PHYSICAL HAZ.	0
PPE	G



Printed: 06/17/2008  
Revision: 06/13/2008  
Supersedes Revision: 06/06/2008  
Date Created: 06/04/2008

### 1. Product and Company Identification

**Product Code:** 1623  
**Product Name:** Klean Strip Green Denatured Alcohol **Rockler SKU: 23942**  
**Manufacturer Information**  
**Company Name:** W. M. Barr  
2105 Channel Avenue  
Memphis, TN 38113  
**Phone Number:** (901)775-0100  
**Emergency Contact:** 3E 24 Hour Emergency Contact (800)451-8346  
**Information:** W.M. Barr Customer Service (800)398-3892  
**Web site address:** www.wmbarr.com  
**Preparer Name:** W.M. Barr EHS Department (901)775-0100  
**Synonyms**  
GKGA75002, QKGA75003

### 2. Composition/Information on Ingredients

Hazardous Components (Chemical Name)	CAS #	Concentration	OSHA PEL	ACGIH TWA	Other Limits
1. Ethyl alcohol {Ethanol}	64-17-5	90.0 -100.0 %	1000 ppm	1000 ppm	No data.
2. Methanol {Methyl alcohol; Carbinol; Wood alcohol}	67-56-1	<10.0 %	200 ppm	200 ppm	No data.
3. Methyl isobutyl ketone {Hexone; Isopropylacetone; MIBK; 4-Methyl-2-pentanone}	108-10-1	<10.0 %	100 ppm	50 ppm	No data.
4. Acetic acid, Ethyl ester {Ethyl acetate}	141-78-6	< 5.0 %	400 ppm	400 ppm	No data.
Hazardous Components (Chemical Name)	RTECS #	OSHA STEL	OSHA CEIL	ACGIH STEL	ACGIH CEIL
1. Ethyl alcohol {Ethanol}	KQ6300000	No data.	No data.	No data.	No data.
2. Methanol {Methyl alcohol; Carbinol; Wood alcohol}	PC1400000	No data.	No data.	250 ppm	No data.
3. Methyl isobutyl ketone {Hexone; Isopropylacetone; MIBK; 4-Methyl-2-pentanone}	SA9275000	No data.	No data.	75 ppm	No data.
4. Acetic acid, Ethyl ester {Ethyl acetate}	AH5425000	No data.	No data.	No data.	No data.

### 3. Hazards Identification

#### Emergency Overview

Danger! Poison. May be fatal or cause blindness if swallowed. Vapor Harmful. Flammable. Eye Irritant.

#### OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

#### Health Hazards (Acute and Chronic)

Inhalation Acute Exposure Effects:

Vapor harmful. May cause dizziness, headache, watering of eyes, irritation of respiratory tract, irritation to the eyes, drowsiness, nausea, other central nervous system effects, spotted vision, dilation of pupils, and convulsions.

Skin Contact Acute Exposure Effects:

May cause irritation, drying of skin, redness, and dermatitis. May cause symptoms listed under inhalation. May be absorbed through damaged skin.

RTD20000423AA

# MATERIAL SAFETY DATA SHEET

## Klean Strip Green Denatured Alcohol

Page: 2

Printed: 06/17/2008

Revision: 06/13/2008

Supersedes Revision: 06/06/2008

Eye Contact Acute Exposure Effects:

May cause irritation.

Ingestion Acute Exposure Effects:

Poison. Cannot be made non-poisonous. May be fatal or cause blindness. May produce fluid in the lungs and pulmonary edema. May cause dizziness, headache, nausea, drowsiness, loss of coordination, stupor, reddening of face and or neck, liver, kidney and heart damage, coma, and death. May produce symptoms listed under inhalation. Prolonged ingestion may cause liver damage, "fetal-alcohol syndrome" in pregnant females and neuronal degeneration. Aspiration into lungs while vomiting, may result in severe pulmonary injury.

Chronic Exposure Effects:

May cause symptoms listed under inhalation, dizziness, fatigue, tremors, permanent central nervous system changes, blindness, pancreatic damage, and death.

### Signs and Symptoms Of Exposure

See Potential Health Effects.

### Medical Conditions Generally Aggravated By Exposure

Diseases of the liver.

## 4. First Aid Measures

### Emergency and First Aid Procedures

Inhalation:

If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.

Skin Contact:

Wash with soap and water while removing contaminated clothing. If symptoms persist seek medical advice.

Eye Contact:

Flush with large quantities of water for at least 15 minutes. Get medical attention.

Ingestion:

Call your poison control center, hospital emergency room or physician immediately for instructions to induce vomiting.

Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

### Note to Physician

Poison. This product contains methanol. Methanol is metabolized to formaldehyde and formic acid. These metabolites may cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used as an antidote. Methanol is effectively removed by hemodialysis. Call your local poison control center for further instructions.

## 5. Fire Fighting Measures

**Flammability Classification:**

OSHA Class IB

**Flash Pt:**

57.00 F Method Used: Unknown

**Explosive Limits:**

LEL: 4 % UEL: 20%

**Autoignition Pt:**

752.00 F

### Special Fire Fighting Procedures

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined area. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

### **Unusual Fire and Explosion Hazards**

Flashback of vapors possible over considerable distance.

### **Hazardous Combustion Products**

Carbon monoxide and carbon dioxide.

### **Extinguishing Media**

Use carbon dioxide, dry powder, alcohol-resistant foam, or water spray.

### **Unsuitable Extinguishing Media**

No data available.

## **6. Accidental Release Measures**

### **Steps To Be Taken In Case Material Is Released Or Spilled**

Clean-up:

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources, keep flares, smoking or flames out of hazard area.

Small spills:

Take up liquid with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

Large spills:

Dike far ahead of spill for later disposal.

Do not flush into surface water or sanitary sewer system.

## **7. Handling and Storage**

### **Precautions To Be Taken in Handling**

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

### **Precautions To Be Taken in Storing**

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

## **8. Exposure Controls/Personal Protection**

### **Respiratory Equipment (Specify Type)**

For OSHA controlled work place and other regular users. Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.

### **Eye Protection**

Safety glasses, chemical goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

### **Protective Gloves**

Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.

### **Other Protective Clothing**

Various application methods can dictate the use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.

# MATERIAL SAFETY DATA SHEET

## Klean Strip Green Denatured Alcohol

Page: 4

Printed: 06/17/2008

Revision: 06/13/2008

Supersedes Revision: 06/06/2008

### Ventilation

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering -- Stop -- ventilation is inadequate. Leave area immediately.

### Work/Hygienic/Maintenance Practices

A source of clean water should be available in the work area for flushing eyes and skin.

Do not eat, drink, or smoke in the work area.

Wash hands thoroughly after use.

Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use.

Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

## 9. Physical and Chemical Properties

**Physical States:** [ ] Gas [X] Liquid [ ] Solid

**Melting Point:** -173.00 F

**Boiling Point:** 165.20 F - 176.00 F

**Autoignition Pt:** 752.00 F

**Flash Pt:** 57.00 F Method Used: Unknown

**Explosive Limits:** LEL: 4 % UEL: 20%

**Specific Gravity:** 0.7968 - 0.8118

**Bulk density:** 6.75 LB/GA

**Vapor Pressure:** ~ 50 MM HG at 20.0 C

**Vapor Density:** ~ 1.5

**Evaporation Rate:** ~ 2

**Solubility in Water:** No data.

### Solubility Notes

Completely soluble in water.

**Percent Volatile:** 100.0 % by weight.

**VOC / Volume:** 789.0000 G/L

**Corrosion Rate:** No data.

**pH:** No data.

### Appearance and Odor

Clear, water white, thin liquid

## 10. Stability and Reactivity

**Stability:** Unstable [ ] Stable [X]

### Conditions To Avoid - Instability

No data available.

### Incompatibility - Materials To Avoid

Incompatible with strong oxidizing agents, inorganic acids, and halogens.

### Hazardous Decomposition Or Byproducts

Decomposition may produce carbon monoxide, carbon dioxide, and possibly other unidentified organic compounds.

**Hazardous Polymerization:** Will occur [ ] Will not occur [X]

### Conditions To Avoid - Hazardous Polymerization

No data available.

## 11. Toxicological Information

No data available.

### Carcinogenicity/Other Information

No data available.

Hazardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
1. Ethyl alcohol {Ethanol}	64-17-5	n.a.	n.a.	A4	n.a.
2. Methanol {Methyl alcohol; Carbinol; Wood alcohol}	67-56-1	n.a.	n.a.	n.a.	n.a.
3. Methyl isobutyl ketone {Hexone; Isopropylacetone; MIBK; 4-Methyl-2-pentanone}	108-10-1	n.a.	n.a.	n.a.	n.a.
4. Acetic acid, Ethyl ester {Ethyl acetate}	141-78-6	n.a.	n.a.	n.a.	n.a.

## 12. Ecological Information

Do not flush into surface water or sanitary sewer system.

Low potential to affect aquatic organisms and secondary waste treatment organisms.

Readily biodegradable.

Not likely to bioconcentrate.

## 13. Disposal Considerations

### Waste Disposal Method

Dispose in accordance with applicable local, state, and federal regulations.

## 14. Transport Information

### LAND TRANSPORT (US DOT)

#### DOT Proper Shipping Name

GKGA75002:  
 UN1170, Ethyl Alcohol, 3, PGII

QKGA75003:  
 UN1170, Ethyle Alcohol, 3, PGII, LTD. QTY.

## 15. Regulatory Information

### US EPA SARA Title III

Hazardous Components (Chemical Name)	CAS #	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110
1. Ethyl alcohol {Ethanol}	64-17-5	No	No	No	No
2. Methanol {Methyl alcohol; Carbinol; Wood alcohol}	67-56-1	No	Yes 5000 LB	Yes	No
3. Methyl isobutyl ketone {Hexone; Isopropylacetone; MIBK; 4-Methyl-2-pentanone}	108-10-1	No	Yes 5000 LB	Yes	Yes
4. Acetic acid, Ethyl ester {Ethyl acetate}	141-78-6	No	Yes 5000 LB	No	No

### SARA (Superfund Amendments and Reauthorization Act of 1986) Lists:

**Sec.302:** EPA SARA Title III Section 302 Extremely Hazardous Chemical with TPQ. \* indicates 10000 LB TPQ if not volatile.

**Sec.304:** EPA SARA Title III Section 304: CERCLA Reportable + Sec.302 with Reportable Quantity. \*\* indicates statutory RQ.

**Sec.313:** EPA SARA Title III Section 313 Toxic Release Inventory. Note: -Cat indicates a member of a chemical category.

**Sec.110:** EPA SARA 110 Superfund Site Priority Contaminant List

### EPA Hazard Categories:

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

**MATERIAL SAFETY DATA SHEET**  
**Klean Strip Green Denatured Alcohol**

Page: 6

Printed: 06/17/2008

Revision: 06/13/2008

Supercedes Revision: 06/06/2008

- Yes  No Acute (immediate) Health Hazard
- Yes  No Chronic (delayed) Health Hazard
- Yes  No Fire Hazard
- Yes  No Sudden Release of Pressure Hazard
- Yes  No Reactive Hazard

**16. Other Information**

**Company Policy or Disclaimer**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.