

MAGNETIC TOUCH LATCH

28407

28381-White
28407-Black
28431-Brown

FEATURES:

- black or white or brown plastic housing
- surface mounts to cabinet side, bottom or underside of fixed shelf-vertical/horizontal
- magnet moves out $\frac{3}{8}$ " from closed position when door is pushed inward activating release
- strike plate is nickel plated and attaches with a single screw
- easy and fast installation
- adjustable
- can be installed on inset/lipped/overlay doors

APPLICATIONS:

A magnetic catch with touch latch feature for cabinet doors.

SPECIFICATIONS:

Note: Side view shows glass door with wrap around finger pull magna strike. This attaches easily to $\frac{1}{4}$ " glass doors and does not require boring a hole thru the glass.

INSTALLATION:

1. Determine location where catch is to be installed. It is best to position latch where hand will normally contact door for opening or closing of door. Position catch to cabinet so that catch with strike plate attached meets the inner surface of door. Hold catch in this set position and mark off with pencil through slotted holes of housing onto cabinet. (See drawing for $1\text{-}5/16$ " set back)
 2. Drill pilot holes and mount catch to cabinet---slotted holes only.
 3. Position strike plate to inside of door to be in line with magnet when door is closed. Mark off screw hole in plate onto door with pencil.
 4. Drill pilot hole. Attach strike plate to door with screw provided.
 5. Check catch operation by opening and closing door. Adjust catch housing by loosening screws and moving housing in or out to get correct closed position of door.
 6. Drill front housing pilot hole. Drive screws through front holes locking housing into a fixed position.
- Note: When installing touch latch for hinged glass door, order No Bore Magnastrike: #30049 polished brass, #30056 satin black or #30064 nickel finish.

